

Hotel Pack Wrapping Machine (MODEL: SVM/W/100)



MODEL: SVM/W/100 (Hotel Pack Wrapping Machine)

This model is suitable for Rectangular, Square, Round, cream biscuits. Biscuits are manually fed into the conveyor. After this process nylon lugs carry biscuits through the adjustable folding box along with biscuits paper for center seal, by the pair of hot sealing rollers. The end sealing and cutting is done by rotating hot jaw.

ELECTRICAL DATA

Heater Load	Motor Load	Total Load	Frequency Drive	Temperature controller
1. Round Heater 400w x 2 = 800w	Hindustan Motors. 3 ph 440v 1.5Hp 1400 RPM current - 2.25 A Or	VA= 440v x 10A 4400VA 4.4 KVA	Telemecanique or L.G. Make 1.5 KW	Shiva Control System Range 0to 380C fek
2. Tube Heater 250w x 8 = 2000w Primary current - 6 A Secondary Current - 2800w Total Load - 56 A	3 ph 220v 1.5 Hp 1400 RPM Current Load - 3.8 A Eltek Make Induction Motor 220 V 1 Phase	5KVA 4kw	230 / 440 V Output 3 phase	

TECHNICAL DATA

Maximum products size	60 mm
Maximum products size	10 mm
Maximum products size	60 mm
Maximum products size	20 mm
Maximum Stack Length	150 mm

WRAPPING MATERIAL:

Heat sealable material such as 40-micron polyester ploy/foil pearlised B.O.P.P., heat sealable B.O.P.P. & Aluminum foil, paper poly and other common composite films with inner heat sealable layer etc.

Maximum Width of Packing material	250 mm
Maximum Width of Packing material	90 mm
Maximum Reel Dia	10 inch

The maximum speed of machine is 250 packets/min.